



ANGORA CARPETS AXMINSTER CARPET SPECIFICATIONS



Construction		Contract Woven Axminster				
Backing Materials	Weft	P.P				
	Warp	Polyester				
Backing Coating		Non-fray latex				
Pile Composition		80% British wool (mothproofed)				
		20% nylon ±3%				
Pitch	7 per inch	7 per inch	7 per inch	7 per inch	7 per inch	7 per inch
Rows	7 per inch	8 per inch	9 per inch	10 per inch	11 per inch	12 per inch
Pile Height Above Backing	0.275 inch(+/-10%) 7 mm.	0.275 inch(+/-10%) 7 mm.	0.275 inch(+/-10%) 7 mm.	0.275 inch(+/-10%) 7 mm.	0.275 inch(+/-10%) 7 mm.	0.275 inch(+/-10%) 7 mm.
Effective Pile Weight	21,60 oz/yd ² (+/-15%) 732 gr/m ²	24,68 oz/yd ² (+/-15%) 837 gr/m ²	27,77 oz/yd ² (+/-15%) 941 gr/m ²	30,86 oz/yd ² (+/-15%) 1046 gr/m ²	33,94 oz/yd ² (+/-15%) 1150 gr/m ²	37,03 oz/yd ² (+/-15%) 1255 gr/m ²
Total Pile Weight	29,31 oz/yd ² (+15%/-10%) 994 gr/m ²	33,50 oz/yd ² (+15%/-10%) 1136 gr/m ²	37,69 oz/yd ² (+15%/-10%) 1278 gr/m ²	41,88 oz/yd ² (+15%/-10%) 1420 gr/m ²	46,07 oz/yd ² (+15%/-10%) 1562 gr/m ²	50,25 oz/yd ² (+15%/-10%) 1704 gr/m ²
Total Carpet Weight	53,29 oz/yd ² (+/-15%) 1807 gr/m ²	57,36 oz/yd ² (+/-15%) 1944 gr/m ²	58,01 oz/yd ² (+/-15%) 1967 gr/m ²	62,20 oz/yd ² (+/-15%) 2109 gr/m ²	64,64 oz/yd ² (+/-15%) 2191 gr/m ²	68,82 oz/yd ² (+/-15%) 2333 gr/m ²
Yarn Count	2 ply	2/47's Dewsbury(+/-5%)				
Loom sizes	3.66 m to 4.0 m		3.66 m to 4.0 m		3.66 m to 4.0 m	
Suitability	General Contract & Extra Very Heavy Contract					
Suitability for stairs	7x9 - 7x10 - 7x11 - 7x12					
Installation method	glue-down or stretching					

Color Fastness	EN 1307	4/5
Light	EN 1307	min. 4
Shampoo	EN 1307	min. 4
Dry Rubbing	EN 1307	min. 4
Wet Rubbing	EN 1307	min. 4
Wear Resistance		
Abrasion Wira	BS 4098	Over 50.000
Dynamic Loading	BS 4052	Max.22% loss after 100 impacts
Dimensional Stability	BS 4682	± 0,25 %
Flammability		
Hot Metal Nut Test	BS 4790	Pass
Methenamine Pill Test	ASTM D2859 / BS 6307	Pass

Static Electricity	Will not normally cause discomfort above 25% RH	
Radiant Panel Test	EN 13501 - 1	C _{fl} - s1
Moth Proofing	EN 1815	Permethrin applied
Performance Features		
Maintenance	See Maintenance Guide.	
Tolerances	Angora Carpets Mills apply strict quality control at all stages of production, in compliance with ISO 9001. however as carpet manufacturing is a complex series of operation, slight variations in the weights quoted must be expected. Specifications are subject to change without notice but this will not have a detrimental effect on the performance of the product.	
Color Match	Although every effort is made to ensure color matching width to width, there may be variation dye batch to dye batch due to the inherent variability of the natural wool used in the blend	